





HIGHLIGHTS HTS

- Versatile, variable options for use.
- Very stable ergo stand.
- Heavy duty steel design.
- Ideal for heavy load.
- Excellent vibration absorption.
- Adjustable glides.
- Several caster versions available.
- Different height adjustment systems.
- "VT" version with tiltable table top support available.
- Treadle bar can be adjusted without tools.
- Stand can be completely disassembled for small transport and storage volume.
- · Quick and easy assembly.

ON REQUEST

- Special heights.
- Special lengths.
- Other colors.
- Table tops for all machine types and classes.
- · Sewing motors.



Table top support, tiltable = version "VT".



Caster version "RO1", thread protected casters integrated into the right foot.

TECHNICAL DATA

• Depth base:

Width:

(left to right)

(front to back)

• Lift range: Sit-down workstation

705 mm (approx. 28 in.)

to 850 mm (approx. 33 in.) without table top.

Stand-up workstation

880 mm (approx. 35 in.)

to 1100 mm (approx. 43 in.), without table top.

Sit-down workstation

475 mm (approx. 19 in.).

Stand-up workstation

575 mm (approx. 23 in.).

• Depth top: 1.) Not tiltable version

(front to back) 400 mm (approx. 16 in.).

2.) Tiltable version "VT".

440 mm (approx. 17 in.),

630 mm (approx. 25 in.),

760 mm (approx. 30 in.), 805 mm (approx. 32 in.)

or 1,205 mm (approx. 47 in.).

Treadle bar: Horizontally adjustable.

• Front support: Basic model short.

• Surface: Powder coated in RAL 9002 grey-white.

Other RAL colours on request.

• Weight: Approx. 16 kg (approx. 35 lbs.) per stand.

Packaging: 1 per box.

Please place extra order for treadles/drawers and other accessories.

Request our CD ROM. It contains a lot of information about KESSLER as well as a detailed product catalog with all options.



Caster version "R075" with vertically adjustable treadle bar.

Casters 360° lockable and thread protected.



Caster version "ROA", thread protected casters attachted to the outside of the right foot.



KESSLER GmbH
Industriegebiet • Auweg 10
D-72362 Nusplingen
Tel.: ++ 49 (0) 74 29 / 93 19 - 0

Fax: ++ 49 (0) 74 29 / 93 19 - 10 www.kessler-ergo.com

info@kessler-ergo.com