



Think Ergonomics



KEG

flexible ♦ stable ♦ versatile

- ♦ Individually variable due to well designed modular system.
- ♦ Height adjustable by hand crank or electric motor (Electro-pillar made of precision processed aluminum profile).
- ♦ Ergonomic individual adjustment possibilities.
- ♦ 10,000 times proven quality.



Pedestal stand, electrically height adjustable.
Model "KEG-EL-H-GL-900.

With vibration absorbing glides
With adjustable table top supports
With height adjustable drawer support

Version "GL".
Version "H".
Version "S 12".



HIGHLIGHTS

- ◆ State-of-the-art design.
- ◆ Sit-down and stand-up workstation.
- ◆ Ideal for heavy load.
- ◆ Excellent vibration absorption.
- ◆ Tilt plates, "VT" version.
- ◆ Separate electrically height adjustable table top.
- ◆ Stand completely pre-assembled.
- ◆ Adapter system for machine integration (on customer's request)
- ◆ Big accessory package.

OPTIONAL

- ◆ Tilt plates, version "VT" +/- 10° (Stand height + approx. 50 mm (approx. 2 in.).)
- ◆ Electrically adjustable work plate. Lift approx. 150 mm (approx. 6 in.).
- ◆ Casters: Caster diameter 100 mm (approx. 4 in.). Twin casters 50, 75, or 100 mm (approx. 2, 3, or 4 in.) in diameter. All casters 360° lockable and thread protected.
- ◆ 4 adjustable glides version "HB", adjustable to a height of 120 mm (approx. 5 in.) (only with KEG).

ON REQUEST

- ◆ Special heights.
- ◆ Special lengths.
- ◆ Other colors.
- ◆ Table tops for all machine types and classes.
- ◆ Sewing motors.

TECHNICAL DATA

- ◆ Lift range: "KEG-GL" 630 mm (approx. 25 in.) to 900 mm (approx. 35 in.), with glides, without table top thickness.
- "KEG-R075" 700 mm (approx. 28 in.) to 970 mm (approx. 38 in.), with casters, without table top thickness.
- "KEG-S" 610 mm (approx. 24 in.) to 880 mm (approx. 35 in.), with glides, without table top thickness.
- "KEG-EL-GL" 630 mm (approx. 25 in.) to 1,030 mm (approx. 41 in.), with glides, without table top thickness.
- "KEG-EL-R075" 700 mm (approx. 28 in.) to 1,100 mm (approx. 38 in.), with casters, without table top thickness.
- "KEG-EL-S" 650 mm (approx. 26 in.) to 1,050 mm (approx. 41 in.), with glides, without table top thickness.
- ◆ Depth top "KEG" 500 mm (approx. 20 in.)
- (front to back): "KEG-S" 670 mm (approx. 26 in.)
- ◆ Standard "KEG" 800 mm (approx. 31 in.) or 900 mm (approx. 35 in.)
- widths: "KEG-S" 900 mm (approx. 35 in.)
- ◆ Surface: Powder coated in RAL 9002 grey-white.
- ◆ Weight: Approx. 35 kg (approx. 77 lbs.) per stand.
- ◆ Packaging: 1 per box.

ACCESSORIES:

- ◆ Drawer support welded on.
- ◆ Height adjustable drawer support.
- ◆ Guiding device for clutch motors.
- ◆ And much more.

Please place extra order for treadles/drawers and other accessories.

Request our CD ROM. It contains a lot of information about KESSLER as well as a detailed product catalog with all options.



Pedestal stand, height adjustable with hand crank, Modell "KEG-SH-VT".

- ◆ With vibration absorbing glides.
- ◆ With adjustable table top supports, version "H".
- ◆ With laterally welded drawer support, version "S 10".
- ◆ With tilt plates, version "VT".



KESSLER GmbH
 Industriegebiet • Auweg 10
 D-72362 Nusplingen
 Tel.: ++ 49 (0) 74 29 / 93 19-0
 Fax: ++ 49 (0) 74 29 / 93 19-10
 www.kessler-ergo.com
 info@kessler-ergo.com