



Think Ergonomics



KES 2100

ergonomic ♦ innovative ♦ adjustable

- ♦ Future oriented top-of-the-line model
- ♦ The ideal sit-down/stand-up workstation for newcomers
- ♦ Manual adjustment by detachable hand crank on both sides
- ♦ Well designed modular system for many different versions



Manual ergo stand, height adjustable by hand crank, model "KES-2100-VT"
Sit-down/stand-up workstation with vibration absorbing glides.
Table top supports, tiltable with clamping levers.
Version "VT" (height + approx. 40 mm ≈ 1.5 in.)



HIGHLIGHTS

- ♦ Versatile in numerous fields of application: e.g. sewing workstation, table for assembly, packing, spreading
- ♦ Heavy duty steel design for ultimate stability
- ♦ Mechanical design, therefore absolutely parallel table top supports
- ♦ No hydraulic or pneumatic system, therefore no leaks
- ♦ Very smooth up and down movement
- ♦ Maintenance-free
- ♦ Stand can be completely disassembled for small transport and storage volume
- ♦ Quick and easy assembly
- ♦ Special models for handling large pieces: e.g. L-shaped tables with 3 legs or U-shaped tables with 4 legs
- ♦ Big accessory package for expanding the modular system: e.g. attachable leg extension, or retrofitting tilt plates
- ♦ Can be shipped via parcel services

ON REQUEST

- ♦ Special heights
- ♦ Special lengths
- ♦ Other colors
- ♦ Table tops for all machine types and classes
- ♦ Sewing motors



Table top support, not tiltable = basic version (Version "VT" can be retrofitted)



Hand crank for height adjustment can be inserted on left or right side of the stand

TECHNICAL DATA

- ♦ Lift range on glides: 685 mm (approx. 27 in.) to 1085 mm (approx. 43 in.), without table top (add 40 mm approx. 1.5 in. for tilt plates)
- ♦ Lift range on casters RO75: 765 mm (approx. 30 in.) to 1165 mm (approx. 46 in.), without table top (add 40 mm approx. 1.5 in. for tilt plates)
- ♦ Height: 400 mm (approx. 16 in.)
- ♦ Load capacity: max. 120 kg (approx. 265 lbs.)
- ♦ Standard width (left to right): 580 mm (approx. 24 in.), 780 mm (approx. 31 in.), 980 mm (approx. 40 in.), or 1,180 mm (approx. 47 in.)
- ♦ Standard depth (front to back): Base 600 mm (approx. 24 in.), top 480 mm (approx. 19 in.)
- ♦ Surface: Powder coated in RAL 9002 grey-white
- ♦ Weight: approx. 26 kg (approx. 58 lbs.)
- ♦ Packaging: 1 per unit = 2 boxes.

OPTIONAL

- ♦ Table top support: tiltable version "VT" +/- 10°
- ♦ Treadle bar: horizontally adjustable
- ♦ Casters: caster diameter 100 mm (4 in.) twin casters 50 mm (2 in.), 75 mm (3 in.), or 100 mm (4 in.) diameter. All casters 360° lockable and thread protected.

Please place extra order for treadles/drawers and other accessories.

Request our CD ROM. It contains a lot of information about KESSLER as well as a detailed product catalog with all options.



KESSLER GmbH
 Industriegebiet • Auweg 10
 D-72362 Nusplingen
 Tel.: ++ 49 (0) 74 29 / 93 19-0
 Fax: ++ 49 (0) 74 29 / 93 19-10
 www.kessler-ergo.com
 info@kessler-ergo.com